


Habiasense // HT5

PTFE insulated, PFA sheathed multicores

Intended for use as internal wiring of equipment or as external or interconnecting wires

Description		Cores			Finished Cable					
HT5	No. of cores	Nickel Plated Copper (NPC)		PTFE	NPC braid	PFA	Weight	Amps	Fixed MBR	Article Number
		Size	Conductor	Insulation	Shield/s	Sheath/s				
600 / 1000V AC U _v /U	Lay up	AWG	Nom Ø	Nom Ø	Ø	Nom Ø	Nom Ø	Nom g/m	mm	Article Number
E 2619 NPC TA 2	2	26	0.48	1.00	-	2.5	9	11	13	700043976
E 2419 NPC TA 2		24	0.60	1.13	-	2.8	12	15	14	700043977
E 2219 NPC TA 2		22	0.76	1.30	-	3.1	16	20	16	700043978
E 2019 NPC TA 2		20	0.96	1.47	-	3.5	21	26	18	700043979
E 2619 NPC TA 3	3	26	0.48	1.00	-	2.7	12	10	14	700043980
E 2419 NPC TA 3		24	0.60	1.13	-	3.0	16	14	15	700043981
E 2219 NPC TA 3		22	0.76	1.30	-	3.3	21	18	17	700043982
E 2019 NPC TA 3		20	0.96	1.47	-	3.7	29	24	19	700043983
E 2619 NPC TA 4	4	26	0.48	1.00	-	2.9	16	10	15	700043984
E 2419 NPC TA 4		24	0.60	1.13	-	3.2	20	13	16	700043985
E 2219 NPC TA 4		22	0.76	1.30	-	3.6	27	17	18	700043986
E 2019 NPC TA 4		20	0.96	1.47	-	4.0	37	22	20	700043987
E 2619 NPC TA 7	7	26	0.48	1.00	-	3.5	25	8	18	700043988
E 2419 NPC TA 7		24	0.60	1.13	-	3.9	33	11	20	700043989
E 2219 NPC TA 7		22	0.76	1.30	-	4.6	48	15	23	700043990
E 2019 NPC TA 7		20	0.96	1.47	-	5.1	66	19	26	700043991
600 / 1000V AC U _v /U	Lay up	AWG	Nom Ø	Nom Ø	Nom Ø	Nom Ø	Nom Ø	Nom g/m	mm	Article Number
E 2619 NPC STA 2	2	26	0.48	1.00	2.5	3.0	16	11	15	700043960
E 2419 NPC STA 2		24	0.60	1.13	2.7	3.2	19	15	16	700043961
E 2219 NPC STA 2		22	0.76	1.30	3.1	3.6	24	20	18	700043962
E 2019 NPC STA 2		20	0.96	1.47	3.4	3.9	30	26	20	700043963
E 2619 NPC STA 3	3	26	0.48	1.00	2.6	3.1	21	10	16	700043964
E 2419 NPC STA 3		24	0.60	1.13	2.9	3.4	25	14	17	700043965
E 2219 NPC STA 3		22	0.76	1.30	3.3	3.8	31	18	19	700043966
E 2019 NPC STA 3		20	0.96	1.47	3.7	4.2	40	24	21	700043967
E 2619 NPC STA 4	4	26	0.48	1.00	2.9	3.4	24	10	17	700043968
E 2419 NPC STA 4		24	0.60	1.13	3.2	3.7	30	13	19	700043969
E 2219 NPC STA 4		22	0.76	1.30	3.6	4.1	38	17	21	700043970
E 2019 NPC STA 4		20	0.96	1.47	4.0	4.7	52	22	24	700043971
E 2619 NPC STA 7	7	26	0.48	1.00	3.5	4.0	35	8	20	700043972
E 2419 NPC STA 7		24	0.60	1.13	3.9	4.6	47	11	23	700043973
E 2219 NPC STA 7		22	0.76	1.30	4.4	5.1	61	15	26	700043974
E 2019 NPC STA 7		20	0.96	1.47	4.9	5.6	81	19	28	700043975



Cable identification									
Cores: 1 st : White, 2 nd : Red, 3 rd : Black, 4 th : Blue, 5 th : Yellow, 6 th : Green, 7 th : Orange									
Sheath: Black									
Marking: Habiasense Description - Cores x Size - Voltage - Screen - Article No. - Year-Week									

Characteristics and key properties									
	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU			All-round chemical resistance	Low smoke generation	Flame retardant	+250°C High temp
									Test voltage 1.5 kV AC

Data indicates nominal values in millimetres (mm) unless otherwise stated.

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use.

Valid at the time of publication, it is subject to change without notice.