




Seaguard LWB VG™ / H-GM29-G








TPS155XL insulated, HFS100 sheathed, shielded, water-blocked cores to VG 95218-T-029G
Intended for use as transversal and partially longitudinal watertight cables

Order reference		Cores					Finished cable			Electrical	
	No. of cores	Tin Plated Copper (TPC)			TPS 155 XL	TPC braid	HFS 100	Weight	DC current rating	Voltage	
		Conductor size			Insulation	Shield/s	Sheath/s		In free air at 40°C		
Description (NSN - if applicable)	Article Number	Lay up	AWG	mm ²	Max Ø	Nom Ø	Nom Ø	Max Ø	Nom g/m	Amps	V AC / DC
H-GM29-G001	30552907010	1	-	35	8.4	10.6	11.6	17.2	580	TBC	600/900
H-GM29-G002	30552907020		-	120	16.0	19.6	20.9	29.0	1,750	TBC	
H-GM29-G003	30552907030		-	185	20.0	24.2	25.5	32.2	2,500	TBC	
H-GM29-G004	30552907040		-	240	23.0	27.6	29.1	35.7	3,050	TBC	

Cable identification

Cores	Black	
Sheath	Black	
Marking	C6126 - Habia Cable - VG95218T029G### - #x#mm ² - VDE-REG.-Nr. 8879 - Batchcode	

Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	
				

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use.
Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.