




Seaguard LWB VG™ / H-GM29-H

ETFE insulated, HFS100 sheathed, shielded, water-blocked multicores to VG 95218-T-029H
Intended for use as transversal and partially longitudinal watertight cables

Order reference		Cores					Finished cable			Electrical	
	No. of cores	Tin Plated Copper (TPC)			ETFE	TPC braid	HFS 100	Weight	DC current rating	Voltage	
		Conductor size			Insulation	Shield/s	Sheath/s		In free air at 40°C		
Description (NSN - if applicable)	Article Number	Lay up	AWG	mm²	Max Ø	Nom Ø	Nom Ø	Max Ø	Nom g/m	Amps	V AC / DC
H-GM29-H016	30552908160	2	-	0.75	1.20	1.50	4.0	8.0	80	TBC	500/900
H-GM29-H001	30552908010		-	1.5	1.68	2.03	5.0	10.7	150	TBC	
H-GM29-H017	30552908170		-	6	3.80	5.15	11.4	17.1	390	TBC	
H-GM29-H021	30552908210	3	-	0.75	1.20	1.50	4.3	8.2	90	TBC	500/900
H-GM29-H002	30552908020		-	1.5	1.68	2.03	5.3	11.0	160	TBC	
H-GM29-H003	30552908030		-	1.5	1.68	2.03	5.3	11.0	160	TBC	
H-GM29-H004	30552908040	4	-	0.50	0.94	1.27	4.3	9.5	110	TBC	500/900
H-GM29-H015	30552908150		-	0.50	0.94	1.27	4.3	6.2	60	TBC	
H-GM29-H005	30552908050		-	1.0	1.32	1.70	5.0	10.3	175	TBC	
H-GM29-H022	30552908220		-	6	3.80	5.15	13.5	19.0	560	TBC	
H-GM29-H018	30552908180	5	-	1.5	1.68	2.03	6.9	11.8	200	TBC	500/900
H-GM29-H019	30552908190		-	1.5	1.68	2.03	6.9	11.8	200	TBC	
H-GM29-H006	30552908060	2	-	1.0	1.32	1.70	13.5	19.0	580	TBC	500/900
H-GM29-H007	30552908070	4	-	6	3.80	5.15					
H-GM29-H008	30552908080	7	-	1.5	1.68	2.03	7.3	13.5	260	TBC	500/900
H-GM29-H008	30552908080	4 x 2	-	0.75	1.20	1.50	8.5	15.0	275	TBC	500/900
H-GM29-H009	30552908090	12	-	1.5	1.68	2.03	9.9	16.4	420	TBC	500/900
H-GM29-H010	30552908100	8 x 2	-	0.75	1.20	1.50	12.6	17.2	360	TBC	500/900
H-GM29-H014	30552908140	19	-	6	3.80	5.15	27.6	33.2	2,040	TBC	500/900
H-GM29-H020	30552908200	10 x 2	-	0.75	1.20	1.50	15.0	22.2	560	TBC	500/900
H-GM29-H011	30552908110	24	-	1.5	1.68	2.03	14.2	21.1	835	TBC	500/900
H-GM29-H023	30552908230	14 x 2	-	0.75	1.20	1.50	15.5	24.6	840	TBC	500/900
H-GM29-H012	30552908120	37	-	0.75	1.20	1.50	12.8	18.6	590	TBC	500/900
H-GM29-H013	30552908130	27 x 2	20	-	0.84	1.19	17.1	22.3	620	TBC	500/900

Cable identification

Cores	Black & numbered	
Sheath	Black	
Marking	C6126 - Habia Cable - VG95218T029H### - #x#mm² - VDE-REG.-Nr. 8879 - Batchcode	

Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	
VG 95218-29 Type H approved	VG 95218-20 Type A approved cores	Fixed MBR 7.5x OD	Current rating under review	

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use.
Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.