


VG 95218-29 Type H / H-GM29-H

ETFE insulated, HFS100 sheathed, shielded, water-blocked multicores to VG 95218-T-029H
Intended for use as transversal and partially longitudinal watertight cables

500 V AC / 500 V DC

Order reference		Cores				Finished cable			Electrical	
		No. of cores	Tin Plated Copper (TPC)		ETFE	TPC braid	HFS 100	Weight	DC resistance	DC current rating
			Conductor size		Insulation	Shield/s	Sheath/s			In free air at 40°C
Description	Article Number	Lay up	mm ² (AWG)	Max Ø	Nom Ø	Nom Ø	Max Ø	Nom g/m	Max Ω/km	Amps
H-GM29-H016	30552908160	2	0.75	1.20	1.50	4.0	8.0	80	37.0	TBC
H-GM29-H001	30552908010		1.5	1.68	2.03	5.0	10.7	150	19.0	TBC
H-GM29-H017	30552908170		6	3.80	5.15	11.4	17.1	390	4.00	TBC
H-GM29-H021	30552908210	3	0.75	1.20	1.50	4.3	8.2	90	37.0	TBC
H-GM29-H002	30552908020		1.5	1.68	2.03	5.3	11.0	160	19.0	TBC
H-GM29-H003	30552908030		1.5	1.68	2.03	5.3	11.0	160	19.0	TBC
H-GM29-H004	30552908040	4	0.50	0.94	1.27	4.3	9.5	110	51.0	TBC
H-GM29-H015	30552908150		0.50	0.94	1.27	4.3	6.2	60	51.0	TBC
H-GM29-H005	30552908050		1.0	1.32	1.70	5.0	10.3	175	27.0	TBC
H-GM29-H022	30552908220		6	3.80	5.15	13.5	19.0	560	4.00	TBC
H-GM29-H018	30552908180	5	1.5	1.68	2.03	6.9	11.8	200	19.0	TBC
H-GM29-H019	30552908190		1.5	1.68	2.03	6.9	11.8	200	19.0	TBC
H-GM29-H006	30552908060	2	1.0	1.32	1.70	13.5	19.0	580	27.0	TBC
		4	6	3.80	5.15				4.00	
H-GM29-H007	30552908070	7	1.5	1.68	2.03	7.3	13.5	260	19.0	TBC
H-GM29-H008	30552908080	4 x 2	0.75	1.20	1.50	8.5	15.0	275	37.0	TBC
H-GM29-H009	30552908090	12	1.5	1.68	2.03	9.9	16.4	420	19.0	TBC
H-GM29-H010	30552908100	8 x 2	0.75	1.20	1.50	12.6	17.2	360	37.0	TBC
H-GM29-H014	30552908140	19	6	3.80	5.15	27.6	33.2	2,040	4.00	TBC
H-GM29-H020	30552908200	10 x 2	0.75	1.20	1.50	15.0	22.2	560	37.0	TBC
H-GM29-H011	30552908110	24	1.5	1.68	2.03	14.2	21.1	835	19.0	TBC
H-GM29-H023	30552908230	14 x 2	0.75	1.20	1.50	15.5	24.6	840	37.0	TBC
H-GM29-H012	30552908120	37	0.75	1.20	1.50	12.8	18.6	590	37.0	TBC
H-GM29-H013	30552908130	27 x 2	- (20)	0.84	1.19	17.1	22.3	620	70.0	TBC

Cable identification

Cores Black & numbered





Sheath Black



Marking C6126 - Habia Cable - VG95218T029H### - #x#mm² - VDE-REG.-Nr. 8879 - Batchcode

Characteristics and key properties

		RoHS REACH LVD		Current rating To Be Confirmed	Fluid resistant Fuel Oil Water		Flame resistant			MBR Fixed = 7.5x Ø Flexing = 15x Ø
Approval VG 95218 Type 29H	Approval VG 95218 Type 20A cores							Temp low -50°C		Temp peak +90°C

DISCLAIMER: This document and its content remain the property of Habia Cable. It may not be used, copied or provided to any other party than the intended recipient, without prior written permission from Habia Cable. The product shown is intended for professional use and is subject to the user's own evaluation for any particular purpose. Information provided indicates nominal, indicative values and cannot be considered a binding representation or warranty for products and their use. Information is considered valid at the time of publication and is subject to change without notice.