

BS3G210 Type CM / B-EE-TE

PTFE insulated and sheathed pairs, triples & quads to BS 3G 210 Type CM & Def Stan 61-12 Pt 8
Intended for use as internal wiring of equipment
1000/1900 V AC

Order reference		Cores				Finished cable			Electrical	
Description	Article Number	No. of cores	Silver Plated Copper (SPC)		PTFE	N/A	PTFE	Weight	DC Resistance	DC Current rating
			Size	Conductor	Insulation	Shield/s	Sheath/s		BS 3G 210	In free air at 40°C
		Lay up	AWG	Nom Ø	Nom Ø	Nom Ø	Nom Ø	Max g/m	Max Ω/km	Amps
B-EE 3207 TE 2	70392123207	2	32	0.24	1.04	-	2.92	10.55	580.00	1.0
B-EE 3007 TE 2	70392123007		30	0.30	1.10	-	3.04	11.58	367.00	1.5
B-EE 2807 TE 2	70392122807		28	0.36	1.18	-	3.16	12.69	253.00	2.5
B-EE 2607 TE 2	70392122607		26 (7s)	0.45	1.25	-	3.34	14.56	165.00	3.0
B-EE 2619 TE 2	70392122619		26 (19s)	0.45	1.30	-	3.44	15.62	135.00	4.0
B-EE 2407 TE 2	70392122407		24 (7s)	0.60	1.40	-	3.64	18.04	91.80	5.0
B-EE 2419 TE 2	70392122419		24 (19s)	0.60	1.40	-	3.64	17.92	93.30	5.0
B-EE 2219 TE 2	70392122219		22	0.75	1.55	-	3.94	22.11	61.00	6.5
B-EE 2019 TE 2	70392122019		20	1.00	1.76	-	4.44	29.90	33.80	9.0
B-EE 1819 TE 2	70392121819		18	1.25	2.05	-	4.94	39.20	21.50	12.0
B-EE 3207 TE 3	70392133207		3	32	0.24	1.04	-	3.11	13.55	580.00
B-EE 3007 TE 3	70392133007	30		0.30	1.10	-	3.24	15.01	367.00	1.5
B-EE 2807 TE 3	70392132807	28		0.38	1.18	-	3.37	16.55	253.00	2.0
B-EE 2607 TE 3	70392132607	26 (7s)		0.45	1.25	-	3.56	19.22	165.00	3.0
B-EE 2619 TE 3	70392132619	26 (19s)		0.48	1.30	-	3.67	20.71	135.00	3.5
B-EE 2407 TE 3	70392132407	24 (7s)		0.60	1.40	-	3.88	24.16	91.80	4.0
B-EE 2419 TE 3	70392132419	24 (19s)		0.60	1.40	-	3.88	23.97	93.30	4.0
B-EE 2219 TE 3	70392132219	22		0.75	1.55	-	4.21	30.00	61.00	5.5
B-EE 2019 TE 3	70392132019	20		1.00	1.76	-	4.75	41.25	33.80	7.5
B-EE 1819 TE 3	70392131819	18		1.25	2.05	-	5.29	54.73	21.50	10.5
B-EE 3207 TE 4	70392143207	4		32	0.24	1.04	-	3.41	16.88	580.00
B-EE 3007 TE 4	70392143007		30	0.30	1.10	-	3.55	18.75	367.00	1.5
B-EE 2807 TE 4	70392142807		28	0.38	1.18	-	3.69	20.74	253.00	2.0
B-EE 2607 TE 4	70392142607		26 (7s)	0.48	1.25	-	3.92	24.37	165.00	2.5
B-EE 2619 TE 4	70392142619		26 (19s)	0.48	1.30	-	4.04	26.32	135.00	3.0
B-EE 2407 TE 4	70392142407		24 (7s)	0.60	1.40	-	4.28	30.86	91.80	4.0
B-EE 2419 TE 4	70392142419		24 (19s)	0.60	1.40	-	4.28	30.61	93.30	4.0
B-EE 2219 TE 4	70392142219		22	0.75	1.55	-	4.64	38.43	61.00	5.0
B-EE 2019 TE 4	70392142019		20	1.00	1.76	-	5.25	53.34	33.80	7.0
B-EE 1819 TE 4	70392141819		18	1.25	2.05	-	5.85	71.10	21.50	9.5

Cable identification

Cores 1st: Red, 2nd: Blue, 3rd: Yellow, 4th: Green



Sheath White



Marking None

Characteristics and key properties

CE	UK CA	RoHS REACH LVD	Current rating	Fluid resistant	Flame resistant	Smoke free	MBR
Approval	Approval		BS 3G 210	Fuel Oil Water			Fixed = 5x Ø Flexing = 10x Ø
BS 3G 210 Type CM	Def Stan 61-12 Part 8					Temp low -75°C	Temp >20,000 hrs +190°C

DISCLAIMER: This document and its content remain the property of Habia Cable. It may not be used, copied or provided to any other party than the intended recipient, without prior written permission from Habia Cable. The product shown is intended for professional use and is subject to the user's own evaluation for any particular purpose. Information provided indicates nominal, indicative values and cannot be considered a binding representation or warranty for products and their use. Information is considered valid at the time of publication and is subject to change without notice.