


FEP / KK

FEP insulated cores, based on: NEMA HP-4
Intended for use as internal wiring of equipment

Order reference		Conductor				Finished wire				Electrical		
		Silver Plated Copper (SPC)				FEP			Weight	DC Resistance	DC Current rating In free air at 40°C	Voltage
		Size		Stranding	Wire	Core	Tolerance					
Description (NSN - if applicable)	Article Number	AWG	mm ²	# x mm	Nom Ø	Nom Ø	Min Ø	Max Ø	Nom g/m	Ω/km	Amps	V AC U ₀ /U
KK 3201	563cc3201	32	0.03	1 x 0.203	0.20	0.94	0.84	1.04	1.8	584.0	4	1000/1900
KK 3207	563cc3207		0.03	7 x 0.079	0.24	0.99	0.89	1.09	1.9	597.1		
KK 3219	563cc3219		0.04	19 x 0.050	0.24	0.99	0.89	1.09	1.9	554.5		
KK 3001	563cc3001	30	0.05	1 x 0.254	0.25	1.02	0.91	1.12	2.1	374.0	6	
KK 3007	563cc3007		0.06	7 x 0.102	0.30	1.07	0.97	1.17	2.3	354.3		
KK 3019	563cc3019		0.06	19 x 0.060	0.30	1.07	0.97	1.17	2.3	347.8		
KK 2801	563cc2801	28	0.08	1 x 0.320	0.32	1.09	0.99	1.19	2.5	232.3	8	
KK 2807	563cc2807		0.09	7 x 0.127	0.38	1.14	1.04	1.24	2.7	223.8		
KK 2819	563cc2819		0.09	19 x 0.079	0.37	1.14	1.04	1.24	2.7	222.1		
KK 2601	563cc2601	26	0.13	1 x 0.404	0.40	1.17	1.07	1.27	3.2	146.0	10	
KK 2607	563cc2607		0.14	7 x 0.160	0.48	1.24	1.14	1.35	3.5	139.8		
KK 2619	563cc2619		0.15	19 x 0.102	0.48	1.24	1.14	1.35	3.6	131.6		
KK 2401	563cc2401	24	0.20	1 x 0.511	0.51	1.27	1.17	1.37	4.1	89.2	13	
KK 2407	563cc2407		0.23	7 x 0.203	0.60	1.37	1.27	1.47	4.6	86.0		
KK 2419	563cc2419		0.24	19 x 0.127	0.60	1.37	1.27	1.47	4.7	83.3		
KK 0,25	563cc0025	-	0.25	14 x 0.15	0.66	1.38	1.28	1.48	4.0	76.9	14	
KK 2201	563cc2201	22	0.32	1 x 0.643	0.64	1.41	1.30	1.52	5.6	56.4	18	
KK 2207	563cc2207		0.35	7 x 0.254	0.76	1.52	1.42	1.63	6.1	54.8		
KK 2219	563cc2219		0.38	19 x 0.160	0.76	1.52	1.42	1.63	6.4	52.2		
KK 0,5	563cc0050	-	0.50	19 x 0.185	0.88	1.68	1.58	1.78	7.0	40.1	21	
KK 2001	563cc2001	20	0.52	1 x 0.813	0.81	1.57	1.47	1.68	7.7	35.1	23	
KK 2007	563cc2007		0.56	7 x 0.320	0.96	1.73	1.63	1.83	8.5	34.1		
KK 2019	563cc2019		0.62	19 x 0.203	0.96	1.73	1.63	1.83	9.0	32.0		
KK 0,75	563cc0075	-	0.75	19 x 0.225	1.13	1.90	1.80	2.00	11	26.7	28	
KK 1801	563cc1801	18	0.82	1 x 1.024	1.02	1.80	1.68	1.93	11	22.2	31	
KK 1807	563cc1807		0.90	7 x 0.404	1.21	2.01	1.88	2.13	12	21.5		
KK 1819	563cc1819		0.96	19 x 0.254	1.20	2.01	1.88	2.13	13	20.4		
KK 1,0	563cc0100	-	1.00	32 x 0.20	1.20	2.05	1.93	2.17	12	20.0	33	
KK 1601	563cc1601	16	1.31	1 x 1.290	1.29	2.11	1.96	2.26	16	14.0	41	
KK 1619	563cc1619		1.23	19 x 0.287	1.36	2.26	2.11	2.41	16	15.8		
KK 1,5	563cc0150	-	1.50	30 x 0.25	1.50	2.35	2.20	2.50	20	13.7	41	
KK 1419	563cc1419	14	1.94	19 x 0.361	1.71	2.69	2.49	2.90	24	10.0	53	

Core identification: Replace 'cc' in the article number with 2 digits below to select from available colours

00 Black 11 Brown 22 Red 33 Orange 44 Yellow 55 Green 66 Blue 77 Violet 88 Grey 99 White 29 Pink

Marking Not applicable

Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	Flame retardant	Low smoke	+200°C High temp
	Complies with NEMA HP-4			Current rating in free air to IEC 60287	-65°C Low temp	

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use. Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.

FEP / KK

FEP insulated cores, based on: NEMA HP-4
Intended for use as internal wiring of equipment

Order reference		Conductor				Finished wire				Electrical		
		Silver Plated Copper (SPC)				FEP			Weight	DC Resistance	DC Current rating In free air at 40°C	Voltage
		Size		Stranding	Wire	Core	Tolerance					
Description (NSN - if applicable)	Article Number	AWG	mm ²	# x mm	Nom ∅	Nom ∅	Min ∅	Max ∅	Nom g/m	Ω/km	Amps	V AC U ₀ /U
KK 2,5	563cc0250	-	2.50	50 x 0.25	1.95	2.88	2.68	3.08	30	8.21	58	1000/1900
KK 1219	563cc1219	12	3.08	19 x 0.455	2.15	3.18	2.97	3.38	36	6.30	71	
KK 1237	563cc1237		2.98	37 x 0.320	2.24	3.12	2.92	3.33	37	6.59		
KK 4	563cc0400	-	4.00	56 x 0.30	2.48	3.45	3.25	3.65	47	5.09	78	
KK 1037	563cc1037	10	4.74	37 x 0.404	2.82	3.68	3.48	3.89	54	4.13	94	
KK 6	563cc0600	-	6.00	84 x 0.30	2.92	4.24	3.99	4.49	66	3.39	102	
KK 8133	563cc8133	8	8.61	133 x 0.287	4.10	5.31	5.05	5.56	98	2.30	140	
KK 10	563cc1000	-	10.0	80 x 0.40	3.93	5.48	5.28	5.68	112	1.95	144	
KK 6133	563cc6133	6	12.6	133 x 0.361	5.13	7.45	7.26	7.65	174	1.46	191	
KK 16	563cc1600	-	16.0	128 x 0.40	5.70	7.45	7.20	7.70	166	1.24	197	
KK 4133	563cc4133	4	21.6	133 x 0.455	6.75	9.12	8.86	9.37	267	0.920	258	
KK 25	563cc2500	-	25.0	196 x 0.40	7.20	8.60	8.34	8.86	300	0.795	270	
KK 2665	563cc2665	2	33.7	665 x 0.254	8.51	10.29	10.03	10.54	376	0.580	339	
KK 1817	563cc1817	1	41.4	817 x 0.254	9.60	12.32	10.07	12.57	469	0.490	391	

Core identification: Replace 'cc' in the article number with 2 digits below to select from available colours

00 Black 11 Brown 22 Red 33 Orange 44 Yellow 55 Green 66 Blue 77 Violet 88 Grey 99 White 29 Pink

Marking Not applicable

Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	Flame retardant	Low smoke	+200°C High temp
	Complies with NEMA HP-4			Current rating in free air to IEC 60287	-65°C Low temp	

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use. Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.