


## PTFE / B-E NPC

PTFE insulated cores to BS 3G 210 Type NB and to Def Stan 61-12 Pt 8  
Insulated wires intended for use as internal wiring of equipment

Order reference		Conductor				Finished wire				Electrical		
		Nickel Plated Copper (NPC)				PTFE			Weight	DC resistance	DC Current rating In free air at 40°C	Voltage
		Size		Stranding	Wire	Core	Tolerance					
Description (NSN - if applicable)	Article Number	AWG	mm <sup>2</sup>	# x mm	Nom ∅	Nom ∅	Min ∅	Max ∅	Max g/m	Ω/km	Amps	V AC U <sub>i</sub> /U
B-E 3207 NPC	586cc3207	32	0.04	7 x 0.080	0.24	0.74	0.64	0.84	0.85	605	1.5	600/1000
B-E 3007 NPC	586cc3007	30	0.06	7 x 0.100	0.30	0.80	0.70	0.90	1.75	377	2.0	
B-E 2807 NPC	586cc2807	28	0.08	7 x 0.120	0.36	0.88	0.76	0.96	2.10	258	2.5	
B-E 2601 NPC	586cc2601	26	0.13	1 x 0.400	0.40	0.90	0.80	1.00	2.56	148	4.0	
B-E 2607 NPC	586cc2607		0.13	7 x 0.150	0.45	0.95	0.85	1.05	2.74	166	4.0	
B-E 2619 NPC	586cc2619		0.15	19 x 0.100	0.50	1.00	0.90	1.10	3.09	139	5.0	
B-E 2407 NPC	586cc2407	24	0.20	7 x 0.200	0.60	1.10	1.00	1.20	3.95	91.2	6.0	
B-E 2419 NPC	586cc2419		0.21	19 x 0.120	0.60	1.10	1.00	1.20	3.89	94.9	6.0	
B-E 2301 NPC	586cc2301	23	0.28	1 x 0.600	0.60	1.10	1.00	1.20	4.38	65.0	7.0	
B-E 2219 NPC	586cc2219	22	0.34	19 x 0.150	0.75	1.25	1.15	1.35	5.44	61.3	8.0	
B-E 2019 NPC	586cc2019	20	0.60	19 x 0.200	1.00	1.50	1.40	1.60	8.43	33.6	11.0	
B-E 1819 NPC	586cc1819	18	0.93	19 x 0.250	1.25	1.75	1.65	1.85	12.11	21.2	15.0	

Core identification: Replace 'cc' in the article number with 2 digits below to select from available colours

00 Black 11 Brown 22 Red 33 Orange 44 Yellow 55 Green 66 Blue 77 Violet 88 Grey 99 White 29 Pink

Marking Not applicable

### Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	Low smoke	Flame retardant	+260°C High temp
	BS 3G 210 Type NB	DSP 61-12 Part 8		Current rating to BS 3G 210	-75°C Low temp	

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use.  
Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.