


## BS3G210 Type B / B-E

PTFE insulated cores, approved to BS 3G 210 Type B and to Def Stan 61-12 Part 8  
Insulated wires intended for use as internal wiring of equipment

600 V AC



Order reference		Conductor				Finished wire				Electrical	
		Silver Plated Copper (SPC)				PTFE			Weight	DC resistance	DC Current rating
		Size	Stranding	Wire	Core	Tolerance		BS 3G 210		In free air at 40°C	
Description	Article Number	AWG	mm <sup>2</sup>	# x mm	Nom Ø	Nom Ø	Min Ø	Max Ø	Max g/m	Max Ω/km	Amps
B-E 3207	537cc3207	32	0.04	7 x 0.080	0.24	0.74	0.64	0.84	0.85	558	1.5
B-E 3007	537cc3007	30	0.06	7 x 0.100	0.30	0.80	0.70	0.90	1.75	353	2.0
B-E 2807	537cc2807	28	0.08	7 x 0.120	0.36	0.88	0.78	0.98	2.10	244	2.5
B-E 2601	537cc2601	26	0.13	1 x 0.400	0.40	0.90	0.80	1.00	2.56	146	4.0
B-E 2607	537cc2607		0.12	7 x 0.150	0.45	0.95	0.85	1.05	2.74	159	4.0
B-E 2619	537cc2619		0.15	19 x 0.100	0.50	1.00	0.90	1.10	3.09	130	5.0
B-E 2407	537cc2407	24	0.22	7 x 0.200	0.60	1.10	1.00	1.20	3.95	88.3	6.0
B-E 2419	537cc2419		0.22	19 x 0.120	0.60	1.10	1.00	1.20	3.89	89.8	6.0
B-E 2301	537cc2301	23	0.28	1 x 0.600	0.60	1.10	1.00	1.20	4.38	64.3	7.0
B-E 2219	537cc2219	22	0.34	19 x 0.150	0.75	1.25	1.15	1.35	5.44	58.6	8.0
B-E 2019	537cc2019	20	0.60	19 x 0.200	1.00	1.50	1.40	1.60	8.43	32.5	11.0
B-E 1819	537cc1819	18	0.93	19 x 0.250	1.25	1.75	1.65	1.85	12.11	20.6	15.0

Core identification: Replace 'cc' in the article number with 2 digits below to select from available colours

00 Black 11 Brown 22 Red 33 Orange 44 Yellow 55 Green 66 Blue 77 Violet 88 Grey 99 White 29 Pink

Marking Not applicable

### Characteristics and key properties

		RoHS REACH LVD		<b>Current rating</b> BS 3G 210	<b>Fluid resistant</b> Fuel Oil Water		<b>Flame resistant</b>		<b>Smoke free</b>	<b>MBR</b> Fixed = 5x Ø Flexing = 10x Ø
<b>Approval</b> BS 3G 210 Type B	<b>Approval</b> Def Stan 61-12 Part 8							<b>Temp low</b> -75°C	<b>Temp</b> >20,000 hrs +190°C	

DISCLAIMER: This document and its content remain the property of Habia Cable. It may not be used, copied or provided to any other party than the intended recipient, without prior written permission from Habia Cable. The product shown is intended for professional use and is subject to the user's own evaluation for any particular purpose. Information provided indicates nominal, indicative values and cannot be considered a binding representation or warranty for products and their use. Information is considered valid at the time of publication and is subject to change without notice.