

PTFE / EE NPC

PTFE insulated cores, based on: NEMA HP-3
Intended for use as internal wiring of equipment

Order reference		Conductor				Finished wire				Electrical		
		Nickel Plated Copper (NPC)				PTFE			Weight	DC resistance	DC Current rating In free air at 40°C	Voltage
		Size		Stranding	Wire	Core	Tolerance					
Description (NSN - if applicable)	Article Number	AWG	mm ²	# x mm	Nom ∅	Nom ∅	Min ∅	Max ∅	Nom g/m	Ω/km	Amps	V AC U ₀ /U
EE 3201 NPC	413cc3201	32	0.03	1 x 0.203	0.20	0.96	0.86	1.07	1.8	580.7	5	1000/1900
EE 3207 NPC	413cc3207		0.04	7 x 0.079	0.24	1.02	0.92	1.12	2.0	610.2		
EE 3219 NPC	413cc3219		0.04	19 x 0.051	0.25	1.02	0.92	1.12	2.0	587.2		
EE 3001 NPC	413cc3001	30	0.05	1 x 0.254	0.25	1.02	0.92	1.12	2.1	360.8	7	
EE 3007 NPC	413cc3007		0.06	7 x 0.102	0.30	1.07	0.97	1.17	2.3	360.8		
EE 3019 NPC	413cc3019		0.06	19 x 0.064	0.32	1.07	0.97	1.17	2.3	367.4		
EE 2801 NPC	413cc2801	28	0.08	1 x 0.320	0.32	1.09	0.99	1.19	2.5	227.6	9	
EE 2807 NPC	413cc2807		0.09	7 x 0.127	0.38	1.14	1.04	1.24	2.9	221.7		
EE 2819 NPC	413cc2819		0.09	19 x 0.079	0.39	1.14	1.04	1.24	2.9	227.3		
EE 2601 NPC	413cc2601	26	0.13	1 x 0.404	0.40	1.17	1.07	1.27	3.2	143.0	11	
EE 2607 NPC	413cc2607		0.14	7 x 0.160	0.48	1.24	1.14	1.35	3.6	138.4		
EE 2619 NPC	413cc2619		0.16	19 x 0.102	0.48	1.24	1.14	1.37	3.8	134.5		
EE 2401 NPC	413cc2401	24	0.20	1 x 0.511	0.51	1.27	1.17	1.37	4.1	89.56	15	
EE 2407 NPC	413cc2407		0.22	7 x 0.203	0.60	1.37	1.27	1.47	4.8	85.30		
EE 2419 NPC	413cc2419		0.24	19 x 0.127	0.60	1.37	1.27	1.50	5.0	82.67		
EE 2201 NPC	413cc2201	22	0.32	1 x 0.643	0.64	1.41	1.30	1.52	5.6	56.43	20	
EE 2207 NPC	413cc2207		0.36	7 x 0.254	0.76	1.52	1.42	1.63	6.4	53.15		
EE 2219 NPC	413cc2219		0.38	19 x 0.160	0.76	1.52	1.42	1.68	6.7	51.50		
EE 0,5 NPC	413cc0050	-	0.50	16 x 0.200	0.88	1.68	1.58	1.78	7.0	40.10	26	
EE 2001 NPC	413cc2001	20	0.52	1 x 0.813	0.81	1.57	1.47	1.68	7.7	35.43	26	
EE 2007 NPC	413cc2007		0.56	7 x 0.320	0.96	1.73	1.63	1.83	8.9	33.46		
EE 2019 NPC	413cc2019		0.60	19 x 0.203	0.96	1.73	1.63	1.83	9.5	31.75		
EE 0,75 NPC	413cc0075	-	0.75	24 x 0.200	1.05	1.90	1.80	2.00	11	26.70	34	
EE 1801 NPC	413cc1801	18	0.82	1 x 1.024	1.02	1.80	1.68	1.93	11	22.27	34	
EE 1807 NPC	413cc1807		0.88	7 x 0.404	1.21	2.00	1.88	2.13	13	21.06		
EE 1819 NPC	413cc1819		0.96	19 x 0.254	1.20	2.00	1.88	2.13	14	19.78		
EE 1601 NPC	413cc1601	16	1.30	1 x 1.287	1.29	2.11	1.96	2.26	16	14.00	45	
EE 1619 NPC	413cc1619		1.23	19 x 0.287	1.36	2.26	2.11	2.41	17	15.51		
EE 1,5 NPC	413cc0150	-	1.50	30 x 0.250	1.50	2.35	2.20	2.50	20	13.70	49	
EE 1419 NPC	413cc1419	14	1.87	19 x 0.361	1.70	2.69	2.49	2.90	24	9.810	59	
EE 2,5 NPC	413cc0250	-	2.50	50 x 0.250	1.95	2.88	2.68	3.08	30	8.210	68	
EE 1219 NPC	413cc1219	12	3.02	19 x 0.455	2.14	3.17	2.97	3.38	36	6.168	78	

Core identification: Replace 'cc' in the article number with 2 digits below to select from available colours

00 Black
11 Brown
22 Red
33 Orange
44 Yellow
55 Green
66 Blue
77 Violet
88 Grey
99 White
29 Pink

Marking Not applicable

Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	Low smoke	Flame retardant	+260°C High temp
	Complies with NEMA HP-3			Current rating to IEC 60287	-65°C Low temp	

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use. Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.