

PTFE / H-REE

PTFE insulated cores, based on: NEMA HP-3
Intended for use as internal wiring of equipment

Order reference		Conductor				Finished wire				Electrical		
		Silver Plated Copper (SPC)				PTFE			Weight	DC resistance	DC Current rating In free air at 40°C	Voltage
		Size		Stranding	Wire	Core		Tolerance				
Description (NSN - if applicable)	Article Number	AWG	mm ²	# x mm	Nom ∅	Nom ∅	Min ∅	Max ∅	Nom g/m	Ω/km	Amps	V AC U ₀ /U
H-REE 3201	313cc3201	32	0.03	1 x 0.203	0.20	0.96	0.86	1.07	1.8	544.6	4	1000/1900
H-REE 3207	313cc3207		0.04	7 x 0.079	0.24	1.02	0.92	1.12	2.0	557.7		
H-REE 3219	313cc3219		0.04	19 x 0.051	0.25	1.02	0.92	1.12	2.0	515.0		
H-REE 3001	313cc3001	30	0.05	1 x 0.254	0.25	1.02	0.92	1.12	2.1	347.7	6	
H-REE 3007	313cc3007		0.06	7 x 0.102	0.30	1.07	0.97	1.17	2.3	328.0		
H-REE 3019	313cc3019		0.06	19 x 0.064	0.32	1.07	0.97	1.17	2.3	323.4		
H-REE 2801	313cc2801	28	0.08	1 x 0.320	0.32	1.09	0.99	1.19	2.5	218.8	8	
H-REE 2807	313cc2807		0.09	7 x 0.127	0.38	1.14	1.04	1.24	2.9	208.6		
H-REE 2819	313cc2819		0.09	19 x 0.079	0.39	1.14	1.04	1.24	2.9	207.0		
H-REE 2601	313cc2601	26	0.13	1 x 0.404	0.40	1.17	1.07	1.27	3.2	137.4	10	
H-REE 2607	313cc2607		0.14	7 x 0.160	0.48	1.24	1.14	1.35	3.6	130.2		
H-REE 2619	313cc2619		0.16	19 x 0.102	0.48	1.24	1.14	1.37	3.8	122.3		
H-REE 2401	313cc2401	24	0.20	1 x 0.511	0.51	1.27	1.17	1.37	4.1	85.95	13	
H-REE 2407	313cc2407		0.22	7 x 0.203	0.60	1.37	1.27	1.47	4.8	80.38		
H-REE 2419	313cc2419		0.24	19 x 0.127	0.60	1.37	1.27	1.50	5.0	77.42		
H-REE 2201	313cc2201	22	0.32	1 x 0.643	0.64	1.41	1.30	1.52	5.6	54.13	17	
H-REE 2207	313cc2207		0.36	7 x 0.254	0.76	1.52	1.42	1.63	6.4	51.18		
H-REE 2219	313cc2219		0.38	19 x 0.160	0.76	1.52	1.42	1.68	6.7	48.55		
H-REE 0,5	313cc0050	-	0.50	19 x 0.185	0.88	1.68	1.58	1.78	7.0	40.10	23	
H-REE 2001	313cc2001	20	0.52	1 x 0.813	0.81	1.57	1.47	1.68	7.7	33.79	23	
H-REE 2007	313cc2007		0.56	7 x 0.320	0.96	1.73	1.63	1.83	8.9	32.18		
H-REE 2019	313cc2019		0.60	19 x 0.203	0.96	1.73	1.63	1.83	9.5	29.85		
H-REE 0,75	313cc0075	-	0.75	19 x 0.226	1.13	1.90	1.80	2.00	11	24.30	29	
H-REE 1801	313cc1801	18	0.82	1 x 1.024	1.02	1.80	1.68	1.93	11	21.39	30	
H-REE 1807	313cc1807		0.88	7 x 0.404	1.21	2.00	1.88	2.13	13	20.21		
H-REE 1819	313cc1819		0.96	19 x 0.254	1.20	2.00	1.88	2.13	14	18.99		
H-REE 1601	313cc1601	16	1.30	1 x 1.287	1.29	2.11	1.96	2.26	16	13.45	40	
H-REE 1619	313cc1619		1.23	19 x 0.287	1.36	2.26	2.11	2.41	17	14.89		
H-REE 1,5	313cc0150	-	1.50	19 x 0.320	1.50	2.35	2.20	2.50	20	13.70	44	
H-REE 1419	313cc1419	14	1.87	19 x 0.361	1.70	2.69	2.49	2.90	24	9.416	53	
H-REE 2,5	313cc0250	-	2.50	61 x 0.225	1.95	2.88	2.68	3.08	30	8.210	60	
H-REE 1219	313cc1219	12	3.02	19 x 0.455	2.14	3.17	2.97	3.38	36	5.938	71	
H-REE 1237	313cc1237		2.97	37 x 0.320	2.17	3.20	2.92	3.32	35	6.201		

Core identification: Replace 'cc' in the article number with 2 digits below to select from available colours

00 Black
11 Brown
22 Red
33 Orange
44 Yellow
55 Green
66 Blue
77 Violet
88 Grey
99 White
29 Pink

Marking Not applicable


Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	Low smoke	Flame retardant	+200°C High temp
	Complies with NEMA HP-3			Current rating to IEC 60287	-65°C Low temp	

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use. Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.

PTFE / H-REE

PTFE insulated cores, based on: NEMA HP-3
Intended for use as internal wiring of equipment


Order reference		Conductor				Finished wire				Electrical		
		Silver Plated Copper (SPC)				PTFE			Weight	DC resistance	DC Current rating In free air at 40°C	Voltage
		Size		Stranding	Wire	Core	Tolerance					
Description (NSN - if applicable)	Article Number	AWG	mm ²	# x mm	Nom ∅	Nom ∅	Min ∅	Max ∅	Nom g/m	Ω/km	Amps	V AC U ₀ /U
H-REE 4	313cc0400	-	4.00	56 x 0.300	2.48	3.50	3.25	3.65	47	5.090	81	1000/1900
H-REE 1037	313cc1037	10	4.74	37 x 0.404	2.80	3.76	3.48	3.89	52	3.904	92	
H-REE 6	313cc0600	-	6.00	84 x 0.300	2.92	4.10	3.99	4.49	66	3.390	103	
H-REE 8133	313cc8133	8	8.60	133 x 0.287	4.10	5.38	5.05	5.56	94	2.169	137	
H-REE 10	313cc1000	-	10.00	80 x 0.400	3.93	5.50	5.30	5.70	124	1.950	145	
H-REE 6133	313cc6133	6	13.61	133 x 0.361	5.15	7.40	7.26	7.65	155	1.371	186	

Core identification: Replace 'cc' in the article number with 2 digits below to select from available colours

00 Black 11 Brown 22 Red 33 Orange 44 Yellow 55 Green 66 Blue 77 Violet 88 Grey 99 White 29 Pink

Marking Not applicable

Characteristics and key properties

	RoHS 2011/65/EU	REACH EC No. 1907/2006	LVD 2014/35/EU	Low smoke	Flame retardant	+200°C High temp
	Complies with NEMA HP-3			Current rating to IEC 60287	-65°C Low temp	

DISCLAIMER: Information is indicative and cannot be considered a binding representation or warranty for products and their use. Valid at the time of publication, it is subject to change without notice. Data indicates nominal values in millimetres (mm) unless otherwise stated.