


## Insulated wires / HDPE

Internal wiring (see individual AWM style for limitations)

Style No.	Rating		Core					Finished cable
Insulated wires	Temp.	Voltage	Conductor	Size		Insulation	Size	
	°C	V AC rms		AWG			Min Avg. T	
			Material	Min	Max	Material	mm	
UL 11470	80	600	-	34	4	HDPE	0.19	 <p>Intended use</p> <p>For further processing into cables</p>

### Characteristics and key properties

<b>CE</b>	<b>UK CA</b>	RoHS REACH LVD			<b>Fluid</b> resistant Fuel Oil Water			<b>Halogen</b> free		<b>MBR</b>  Fixed = 5x Ø Flexing = 10x Ø
<b>Certified</b>  UL 758							<b>Temp</b> low <b>-55°C</b>	<b>Temp</b> >20,000 hrs <b>+80°C</b>		

DISCLAIMER: This document and its content remain the property of Habia Cable. It may not be used, copied or provided to any other party than the intended recipient, without prior written permission from Habia Cable. The product shown is intended for professional use and is subject to the user's own evaluation for any particular purpose. Information provided indicates nominal, indicative values and cannot be considered a binding representation or warranty for products and their use. Information is considered valid at the time of publication and is subject to change without notice.