




Insulated wires / PFA

Internal wiring (see individual AWM style for limitations)

Style No.	Rating		Core					Finished cable
	Temp.	Voltage	Conductor	Size		Insulation	Size	
				°C	V AC rms		Material	Min
UL 1716	105	150	- or 150°C Litz wire	50 19 14 9	20 15 10 6	PFA	0.14 0.20 0.33 0.51	 <p>Internal wiring, where not subject to movement or mechanical damage. May also be used for further processing in cables and lead wire for UL 1950 applications Tag may indicate "300V peak - For electronic use only". "Suitable for immersion in gasoline; gasoline vapour; and 60°C or 80°C in oil"</p>
UL 1857	150	150	-	32	16	PFA	0.26	
UL 1858		300	CU TPC	32	10	PFA	0.33	Internal wiring
UL 1859		600	CU TPC	32 8 1	10 2 4/0	PFA	0.51 0.76 1.14	Internal wiring
UL 1708	200	VNS	-	32	20	PFA	0.13	Internal wiring
UL 1707		30	-	32	20	PFA	0.13	Internal wiring of Class 2 circuits in electrical equipment
UL 1860		150	-	32	16	PFA	0.26	Internal wiring
UL 1709		300	-	32	10	PFA	0.33	Internal wiring
UL 1710		600	-	32 8 1	10 2 4/0	PFA	0.51 0.76 1.14	Internal wiring
UL 10313			- or Litz wire	40	9	PFA	0.23	Internal wiring Tag may indicate "600V peak - For electronic use only"
UL 5431		1000	-	36 8 6 1	9 7 2 4/0	PFA	0.51 1.14 1.52 2.03	Internal wiring
UL 1882		250	150	-	36	16	PFA	0.26
UL 1726	300		-	32 8 4 1	10 6 2 4/0	PFA	0.33 0.51 0.76 1.14	Internal wiring
UL 1727	600		-	32 8 1	10 2 4/0	PFA	0.51 0.76 1.14	Internal wiring

Characteristics and key properties

		RoHS REACH LVD			Fluid resistant Fuel Oil Water		Flame resistant		Smoke free	MBR Fixed = 5x Ø Flexing = 10x Ø
Certified UL 758								Temp low -55°C	Temp >20,000 hrs +250°C	

DISCLAIMER: This document and its content remain the property of Habia Cable. It may not be used, copied or provided to any other party than the intended recipient, without prior written permission from Habia Cable. The product shown is intended for professional use and is subject to the user's own evaluation for any particular purpose. Information provided indicates nominal, indicative values and cannot be considered a binding representation or warranty for products and their use. Information is considered valid at the time of publication and is subject to change without notice.